

**PETROLEUM NAPHTHA
SPRAY**

An aerosol product with an applicator to be used in hard-to-reach areas. Perfectly dissolves and removes lubricants and technical oils. It is used for cleaning elements of the brake system, clutch and drive, glued and sealed elements, starters, alternators, carburettors, petrol pumps and engine parts from grease, oils and brake fluid. It is used for cleaning ceramics and degreasing glass and metal before bonding.

PRODUCT COLOUR

Clear.

INSTRUCTION FOR USE

Shake the container for 2-3 minutes before use. Apply the remover to the element to be cleaned and wait until it flows down. Allow to dry or wipe with a dry towel. Repeat the action if necessary.

ATTENTION! Application temperature 5-30°C.

STORAGE CONDITIONS

Shelf life in original container at a temperature of 20°C is:

✓ 5 years.

Store in a dark and dry place away from sources of fire and heat.

HEALTH AND SAFETY REGULATIONS

According to the Material Safety Data Sheet for particular product.

PACKAGING

ITEM NO	TYPE	CAPACITY (ML)	PACKAGING (PCS)	PACKAGING (KG)
80179-5	Petroleum ether spray	500	20	8.4

The information given is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.