

TECHNICAL DATA SHEET**MAT & CLEAN
PRE-CLEANER AND
MATTING PASTE**

A paste that prepares the surface before painting. The product is designed to mat the surface before painting. Cleans all traces of wax, grease and silicone and simultaneously mats the surface during one process.

A product of high quality and effectiveness.

GROUND TYPES

- ◆ Acrylic primers.
- ◆ Epoxy primers.
- ◆ Old paint coats.
- ◆ Plastics (ABS, ABS-PC, PP-EPDM, PUR-RIM, PUR, PVC hard).

COLOUR

- ◆ Green.

SURFACE PREPARATION

Clean the surfaces of dirt, dust, etc. Degrease with a silicone remover.

NOTE: The application temperature must be at least + 10 ° C. Max. air humidity is 80%.

INSTRUCTION FOR USE

By hand:

- ◆ Apply with an abrasive cloth (Scotchbrite) or sponge.
- ◆ Spread evenly over the entire surface.
- ◆ Grind with smooth, round movements, applying light pressure to the surface.
- ◆ When the process is finished, wash the residue with a wet sponge.

TECHNICAL DATA SHEET

By machine:

- ◆ Apply with a fine abrasive cloth.
- ◆ Spread evenly over the entire surface.
- ◆ Grind the surface with a machine of eccentric motion, at low speed.
- ◆ When the process is finished, wash the residue with a wet sponge.

VOC REGULATION

Limit value EU: category B/a 200 g/l

This product contains max. 188 g/l

STORAGE CONDITIONS

The shelf life of the product in original package at the temperature of 20°C is 24 months.

HEALTH AND SAFETY RECOMMENDATIONS

According to Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. no:
00801-3

Package:
1 kg

Bulk pack:
8

This information is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.