

TECHNICAL DATA SHEET**EPOXY PRIMER
SPRAY**

One component primer drying by oxidation, to be used in automotive sector and industry. Anti-corrosion primer of excellent adhesion, creating ideal coat of exceptional corrosion resistance. Suitable also for MDF boards, chipboards, (primed) hard plastics and old paint coats.

PRODUCT CHARACTERISTICS

Excellent adhesion also to “problematic metal surfaces” such as galvanized steel, stainless steel, aluminium etc. Quick drying, easy to process. It has good filling properties, good flexibility, hardness and anti-corrosion properties. It can be overcoated with most of available paints and coats.

COLOUR

Grey

INSTRUCTION FOR USE

- ◆ Due to product’s consistency shake carefully the container before use [for about 5 min.]
- ◆ Ensure that the surface is dry, clean, free from oil, grease, etc. The surface should be sanded.
- ◆ Spray from the distance of about 15 cm, cross, several layers.
- ◆ Leave for drying.
- ◆ Sand the coat a little to ensure better adhesion of the next layer.

ATTENTION! Due to health and safety reasons and to ensure good drying conditions, this product should be used in well ventilated rooms.

DRYING TIME

Dust free: 40 min.

Sandable after: 8 h

Completely dry: 12 h

STORAGE CONDITIONS

Store in a dark and cool place away from fire and heat sources. The shelf life in original package in the temperature of 20°C is 60 months.

TECHNICAL DATA SHEET**HEALTH AND SAFETY RECOMMENDATIONS**

According to Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No	Capacity, ml	Package, pieces:	Package weight, kg:
10606	400	12	7,50

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.