

**TECHNICAL DATA SHEET****Silicone remover**

A mixture of organic solvents. The product effectively removes all types of contamination, including fat and silicone, remaining on metal surfaces and varnished surfaces.

The product is intended for removing impurities such as silicone, Teflon, oils and greases from surfaces to be varnished.

**SUBSTRATE**

---

- ◆ plastics,
- ◆ steel,
- ◆ aluminium,
- ◆ galvanized steel,
- ◆ stainless steel,
- ◆ acrylic primers,
- ◆ filler coatings,
- ◆ old paint coats.

**COLOUR**

---

Clear.

**INSTRUCTION FOR USE**

---

Apply the preparation to a cloth (or other type of cleaning wiper) and wash off any dirt remaining on the surface of the cleaned substrate. Immediately after applying the product, wipe the surface dry with another clean piece of well-absorbent wiping cloth.

It is necessary to change the cleaning cloth frequently and regularly.

**CONTENT OF VOLATILE ORGANIC COMPOUNDS**

---

VOC II/B/a limit = 850 g/l, VOC = 740 g/l

**STORAGE CONDITIONS**

---

Store in a dark and dry place, away from fire and heat sources. The shelf life in original package at the temperature of 20°C is 24 months.

**TECHNICAL DATA SHEET****HEALTH AND SAFETY RECOMMENDATIONS**

According to Material Safety Data Sheet of Dangerous Substance for particular product.

**PACKAGING:**

Item. No:	Capacity:	Package, pieces:	Weight of package, kg:
40504	1 L	6	6,20
40505	5 L	4	20,00

This information is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.