

TECHNICAL DATA SHEET

FADE OUT THINNER SPRAY

A thinner designed for eliminating optical colour differences between an old paint coat and newly applied acrylic clear coat.

FOR PROFESSIONAL USE!

PRODUCT CHARACTERISTICS

- ◆ Easy to use.
- ◆ It can be used with colored varnishes and clear coats.
- ◆ Excellent properties of removing paint overspray.
- ◆ High quality finish.
- ◆ It can be used with most modern coats 2-k and 1-k, but it is always necessary to test the fade out thinner spray before using it with various types of varnishes.

ATTENTION! The product contains acetone; it can dissolve or discolour surfaces such as varnishes for plastics, varnish coatings, textile paints, etc. Therefore, first try the product on the invisible spot of the surface.

BASIS

Solvents and special surfactants wetting / increasing leveling / preventing the formation of craters.

INSTRUCTION FOR USE

- ◆ Use at room temperature.
- ◆ Shake before use.
- ◆ Use the fade out thinner on the edge of the varnish coat to blend the edges or dissolve paint overspray.
- ◆ DO NOT APPLY with a thick layer.
- ◆ Polish the shaded surface with a dry, lint-free cloth.
- ◆ Allow to evaporate / dry.

ATTENTION! Application temperature 8°C ÷ 25°C

STORAGE CONDITIONS

Store in a dark and dry place away from fire and heat sources. Shelf life in original package at the temperature of 20°C is 60 months.

TECHNICAL DATA SHEET**HEALTH AND SAFETY RECOMMENDATIONS**

Follow the Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No	Capacity, ml	Package, pieces:	Package weight, kg:
40603	400	12	5,20

This information is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.