

KARTA TECHNICZNA**ADHESIVE CONTACT
SPRAY**

Transparent adhesive spray, based on styrene butadiene rubber, resins and hydrocarbon solvents.

Bonds a wide range of materials such as: wood, stone, rubber, canvas, cardboard, metal, paper, cork, foam, etc.

FOR PROFESSIONAL USE!

PRODUCT CHARACTERISTICS

- ◆ Easy and clean in use.
- ◆ Strong binding.
- ◆ Quick adhesion.
- ◆ Moisture resistant.
- ◆ Low viscosity adhesive.

ATTENTION: Safe to use on most surfaces and materials. However, the adhesive can damage some materials, so surfaces must always be checked first in an invisible place.

GROUND PREPARATION

- ◆ Clean and degrease the ground
- ◆ For a better effect, the ground can be sanded with p400 paper.

INSTRUCTION FOR USE

- ◆ Shake before use for about 1 minute.
- ◆ Spray the surface / object to be glued.
- ◆ Leave to evaporate for ca. 5 minutes.
- ◆ Stick the surfaces firmly together.
- ◆ Remove the excess of the adhesive with white spirit.
- ◆ Clean the sprayer after painting by putting the container upside down and pressing the valve for approx. 5 seconds.
- ◆ Application temperature (10°C - 35°C)

KARTA TECHNICZNA**PERFORMANCE**

400 ml, $\pm 1.1 \text{ m}^2$ **CONTENT OF VOLATILE ORGANIC COMPOUNDS**

VOC II/B/e limit = 840 g/l, VOC = 587.7 g/l

STORAGE CONDITIONS

Store in a cool (10°C-20°C) and dry place, away from the sources of fire and heat. The shelf life of the product in originally sealed container at 20°C is 60 months.

HEALTH AND SAFETY REGULATIONS

According to Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No:	Capacity, ml:	Package, psc.:	Weight of carton, kg:
80606	400	12	5.20

The information provided is based on careful laboratory research and many years of experience. A strong market position does not absolve us from constant quality control of our products. However, we are not responsible for the final effects if used incorrectly.